ROGUE
Frame only without shock

FRAME SIZE	EAN	SKU
S -size	6979246610455	ROFSMBAA
M -size	6979246610462	ROFMMBAA
L -size	6979246610479	ROFLMBAA
XL-size	6979246610486	ROFXMBAA

WHATS INCLUDED

Rogue carbon frame
16T CNC idler with idler guide
FSA No.57 ZS44/56 headset
Rogue motor cover
Rogue charge port cover
12X148 rear thru axle
UDH Hanger
Bottle cage screws
Seatpost clamp
Cable lugs

Dji avinox M1 motor 250W 105Nm
Dji avinox chainwheel spider with lock
Dji avinox isis crank 155mm
Dji avinox battery 36V 800Wh
Dji DP100 2inch smart screen
Dji BC100 bluetooth remoter X2
Dji speed sensor
Dji 4A 168Wh charger
Dji power cables
Velduro steel chainwheel, 104BCD, 34T

SPEC SUITABLE LIST

Handle System

External wiring headset, ZS, dia top 44mm/ bottom 56mm

Suspension System

1.5T, 160-180mm travel fork suitable, 170mm travel as suggest, CTA:584mm
Shock 205mmX65mm(TR)*, bushing as M8*30mm
65mm travel shock max to 172mm rear travel
62.5mm travel shock as 160mm rear travel

Saddle System

Dia 31.6mm, Seatpost insert length:
S:262mm, M:282mm, L: 302mm, XL:325mm
Dropper cable length: 1200mm
Dropper travel suggest as below
S:180mm, M&L:210mm , XL:240mm

Brake System

Frame rear brake post mount 200mm directly
Front brake cable 850mm
Rear brake cable 1700mm

Drive System

Chainwheel: 104BCD, up to 34T
Crank: up to 165mm length, Min offset:25mm
UDH deralleur suitable
1x shifting only
Shimano and SRAM shift both fit
e-shift and manual shift both fit
Manual shift cable length 2000mm

Wheel System

Front hub: depends on the fork, normally 15X110mm
Rear hub: 12X148 boost, 6-Bolts
Front rim: 29'(700C) rim
Rear rim: 29'(700C) or 27.5(650B) rim
Front tire: depends on your fork
Rear tire: max to 29'X2.4 or 27.5'X2.4

*Please refer to the official website or consult the authorized dealer for the rear shock compatibility list.